



FOLDING CLOSURES AVANT GARDE GRILLE



FREECALL 1800 396 264



FOLDING CLOSURES AVANT GARDE GRILLE

Dynamic Closures offers a comprehensive range of commercial Folding Doors and Grilles closures to suit a variety of internal or external situations such as bars, receptions, gaming areas and cafés and can be easily fitted to wide openings. There are no floor tracks, removable mullions, or the need for complicated bulkheads. The **Folding Closures Range** of doors give greater flexibility in design, as they can effectively be curved to a radius opening and can be operated without the need for costly motorisation.

SPECIFICATIONS

Supply and install AVANT GARDE® Sliding Folding Closure as manufactured by Dynamic Closures (Aust) Pty. Ltd. (specify).

WORK EXCLUDED (Unless otherwise specified)

Preparation of openings to receive sliding closures, including wood or steel supports, access panels or trim work.

CURTAIN INFILL SPECIFICATIONS

> SLIMLINE

Design shall incorporate 205mm O/A (w) x 101mm (h) truss-like aluminium panels at top and bottom of grille. Curtain sections shall be 205mm (w) with a spaced height according to requirements.

> WIDE BODY

Design shall incorporate 285mm O/A (w) x 101mm (h) truss-like aluminium panels at top and bottom of grille. Curtain sections shall be 285mm (w) with a spaced height according to requirements.

GENERAL SPECIFICATIONS

TRACK

The track is to be of extruded aluminium 38mm (h) x 36mm (w). Curved tracks where required are supplied with a standard radius. To provide smooth and easy operation for custom curved applications, the radius must be nominated (minimum 1500mm). For elliptical curves, a template must be provided to Dynamic Closures prior to manufacture.

CURTAIN EDGES

Shall be connected to 32mm x 53mm extruded vertical members. Where stacking pockets are used, the trailing end of the curtain shall be provided with a top and bottom automatically retractable locking post. One intermediate member shall be provided for every 3000mm of opening. All intermediate members shall be fitted with adjustable concealed drop bolts (patented). Intermediate member spacing on counter applications 1800mm max.

LOCKING

Leading posts shall be provided with cylinder locks and guards operable from both sides. Master keyed cylinders, if required, shall be supplied by others. Dust-proof floor sockets shall be provided.

FINISH

- > Standard finish is Clear Anodised.
- > Powder coating to standard Dulux® colours available.
- > Anodising in colours an optional extra.

OPTIONAL EXTRAS

- > Some special finishes may extend delivery period.
- > Egress doors for emergency exits (patented).
- > Tapered openings.