



## DYNASTY® 9400 (SIDE HINGED BI-FOLDING DOOR)



**FREECALL 1800 396 264**



## DYNASTY® 9400 (SIDE HINGED BI-FOLDING DOOR)

The **Dynasty 9400 Series** is versatile and easy to operate. There are no floor tracks, removable mullions, or the need for complicated bulkheads, giving greater flexibility in design and operation, as there's no need for costly motorisation. Suitable for a variety of internal and external situations such as bars, gaming areas, cafés and more, this is one of our most popular doors for wide openings.

### SPECIFICATIONS

Supply and install DYNASTY® Model 9400 by Dynamic Closures (specify).

### WORK EXCLUDED

The general contractor shall supply adequate wood or metal supports. Minimum structural capacity to support (145kg per linear metre of door).

### CONSTRUCTION

Meeting stiles shall be interlocking extruded aluminium members (32mm x 73mm). Sections shall be extruded from aluminium and constructed in accordance with details shown on shop drawings. Should fixed panels be required they shall be of matching construction. Brush weather seal at floor optional.

### PANELS

Available in the following materials:

- 9460 (6.38mm) Clear Laminated Glass
- 9410 (3mm) Clear Tempered Glass
- 9420 (6.38mm) Clear Laminated Glass
- 9430 (3mm) Polycarbonate
- 9440 (6mm) Polycarbonate
- 9450 18ga. Perforated (51%) Visibility Panels

Note: 3mm glass panel material may require a centre horizontal mullion for added strength. All other materials listed may be supplied full height.

Maximum height 2700mm.

### TRACK

Track shall be heavy-duty aluminium [40 (h) mm x 34 (w) mm] extra strength material and shall be surface mounted or recessed as required (specify).

### HARDWARE

To be Dynamic's heavy duty auto retractable cylinder locks on access panels. All other panels shall be secured with a conveniently located shootbolt system that will lock into a specially designed dust resistant floor socket.

### FINISH

All models are offered in our standard high quality clear anodised finish, or standard powder coat finishes.

### LAYOUT

STACK WIDTH: Panel size plus 80mm

STACK DEPTH: 90mm per pair of panels

Example of a 514mm Panel:

PANELS	STACK WIDTH	STACK DEPTH
4	594mm	180mm
6	594mm	270mm
12	594mm	270mm <sup>†</sup>

- > It is imperative that ceiling and floor are level.
- > Stacks left and/or right off wall.
- > Also available in bi-part stacking half left & half right.
- \* Max. openings to 3,500mm wide do not require floor guides.
- \* Counter height or window situations only, may be
- † Each side for double sided stack.

### ■ SINGLE SIDED STACK

