



## DYNASTY 9400 SERIES (SIDE HINGED BI-FOLDING DOOR)



<b>Melbourne</b>	ph: (03) 9739 5222	fax: (03) 9739 5599
<b>Sydney</b>	ph: (02) 9899 2216	fax: (02) 9899 2246
<b>Brisbane</b>	ph: (07) 3805 8055	fax: (07) 3805 8015
<b>Perth</b>	ph: (08) 9343 8329	fax: (08) 9343 1725
<b>Adelaide</b>	ph: (08) 8326 2266	fax: (08) 8384 3570

**FREECALL 1800 651 649**

All openings for the Dynasty must be square & level & prepared to manufacturer's tolerances. Specification correct at time of printing. May alter without notice.



## DYNASTY 9400 SERIES (SIDE HINGED BI-FOLDING DOOR)

Dynamic's **DYNASTY® RANGE** of sliding closures are versatile and easy to operate. There are no floor tracks, removable mullions, or the need for complicated bulkheads. The **DYNASTY® RANGE** of doors give great flexibility in design and can be operated without the need for costly motorisation. Our products suit a variety of internal or external situations such as bars, receptions, gaming areas and cafés and are well suited to wide openings.

### SPECIFICATIONS

Supply and install **DYNASTY® Model 9400** by Dynamic Closures (specify).

### WORK EXCLUDED

The general contractor shall supply adequate wood or metal supports. Minimum structural capacity to support (145kg per linear metre of door).

### CONSTRUCTION

Meeting stiles shall be interlocking extruded aluminium members (32mm x 73mm). Sections shall be extruded from aluminium and constructed in accordance with details shown on shop drawings. Should fixed panels be required they shall be of matching construction. Brush weather seal at floor optional.

### PANELS

Available in the following materials:  
6.38mm Clear Laminated Glass  
18ga. Perforated (51%) Visibility Panels

**Note: Maximum height 3000mm.**

### TRACK

Track shall be heavy-duty extruded aluminium [40 (h) mm x 36 (w) mm] and shall be surface mounted or recessed as required (specify).

### HARDWARE

To be Dynamic's heavy duty auto retractable cylinder locks on access panels. All other panels shall be secured with a conveniently located shootbolt system that will lock into a specially designed dust resistant floor socket.

### FINISH

All models are offered in our standard high quality clear anodised finish, or standard powder coat finishes.

### LAYOUT

**STACK WIDTH:** Panel size plus 80mm

**STACK DEPTH:** 90mm per pair of panels

Example of a 514mm Panel:

PANELS	STACK WIDTH	STACK DEPTH
4	594mm	180mm
6	594mm	270mm
12	594mm	270mm <sup>†</sup>

- > It is imperative that ceiling and floor are level.
- > Stacks left and/or right off wall.
- > Also available in bi-part stacking half left & half right.

\* No floor guides required for a 3000mm max. opening width in a single stack.

### ■ SINGLE SIDED STACK

