

ROLL & FOLD Clear Partition

General

Summary

- A **Style:** Manual folding partition.
- B **Lock Cylinders:** Standard Keyed Mortise Cylinders
Custom Cylinders: All cylinders provided by customer must be delivered to Dynamic prior to manufacturing for fitting to door to ensure Warranty Conditions
- C **Site preparation:** Track support, storage pockets/cupboards and other miscellaneous structural or finish work is the responsibility of others.

Submittals

- A By Others:
 - 1 Shop Drawings: Include plans, elevations, required clearances and accessories.
 - 2 Site Requirements including inductions and access
 - 3 Installation Instructions: If Required.
- B Manufacturer and Installer Qualifications: If Required.
- C Installation Certificates.

Quality Assurance

- A Manufacturer Qualifications: Minimum of three years experience in the fabrication and installation of Side Folding Security Door.
- B Installer Qualifications: Authorized representative of the manufacturer.
- C Pre-installation Conference: A Dynamic Representative will contact the provided Site Foreman/Contact just prior to commencement of field operations to establish procedures to maintain optimum working conditions and to coordinate this work with related and adjacent work.

Warranty

- A Limited Warranty: Two year from the time of installation for defective materials and workmanship.

Execution

Examination

- A Examine supports and other conditions under which Doors are to be installed.
- B Coordinate with responsible entity to correct unsatisfactory conditions and do not proceed with installation until conditions are corrected.

Installation

Follow manufacturer's installation instructions and approved shop drawings.

Adjusting

Test operation of Door and adjust as necessary to provide smooth and proper operation.

Demonstration

Instruct Owner's personnel in proper operating and maintenance procedures.

Some technical pages are under development. For any further queries please contact our specialists'. **FRECALL 1800 651 649.**

V21117



Image Coming Soon

Products

Models & Materials

- A Model: ROLL & FOLD CLEAR PARTITION
- B Construction: Framed with extruded aluminium members (32mm x 72mm). Panels to be connected by steel hinges at each corner allowing a maximum pivot angle of 150 degrees for stability. Bottom hinges shall have 50mm non marking rollers.
- C Panels: Shall be glazed with 3mm Polycarbonate Sheet with 100% viewable area.
Panel Height: Variable to 2000mm.
- D Locking: End panels shall incorporate Dynamic's heavy duty auto retractable cylinder locks or optional Egress Handle. All other panels shall be secured with a conveniently located shootbolt system that will lock into a specially designed dust resistant floor socket. Master keyed cylinders (if required) shall be supplied by others.
- E Finish: Standard finish is clear anodized. Powder coating (Dulux Colour Range) and Anodizing in colours is an optional extra.
- F Operation: Manual pull – push operation. All Roll & Folds must be operated and moved by 2 persons once all Bracing Brackets are engaged.

LOCAL REPRESENTATIVE



Dynamic Closures (Aust) Pty Ltd

Freecall 1800 651 649

Phone 03 9739 5222

Fax 03 9739 5599

E-mail administration@dynamicclosures.com.au