

# SECURASHUTTER Roller Shutters

## General

### Summary

- A **Section Includes:** Roll up aluminium security door.
- B **Lock Cylinders:** Standard Keyed Mortise Cylinders  
Custom Cylinders: All cylinders provided by customer must be delivered to Dynamic prior to manufacturing for fitting to door to ensure Warranty Conditions
- C **Site preparation:** Track support, storage pockets/cupboards and other miscellaneous structural or finish work is the responsibility of others.

### Submittals

- A By Others:
  - 1 Shop Drawings: Include plans, elevations, required clearances and accessories.
  - 2 Site Requirements including inductions and access
  - 3 Installation Instructions: If Required.
- B Manufacturer and Installer Qualifications: If Required.
- C Installation Certificates.

### Quality Assurance

- A Manufacturer Qualifications: Minimum of three years experience in the fabrication and installation of Side Folding Security Door.
- B Installer Qualifications: Authorized representative of the manufacturer.
- C Pre-installation Conference: A Dynamic Representative will contact the provided Site Foreman/Contact just prior to commencement of field operations to establish procedures to maintain optimum working conditions and to coordinate this work with related and adjacent work.

### Warranty

- A Limited Warranty: Two year from the time of installation for defective materials and workmanship.

## Execution

### Examination

- A Examine supports and other conditions under which Doors are to be installed.
- B Coordinate with responsible entity to correct unsatisfactory conditions and do not proceed with installation until conditions are corrected.

### Installation

Follow manufacturer's installation instructions and approved shop drawings.

### Adjusting

Test operation of Door and adjust as necessary to provide smooth and proper operation.

### Demonstration

Instruct Owner's personnel in proper operating and maintenance procedures.

Some technical pages are under development. For any further queries please contact our specialists'. **FREECALL 1800 651 649.**



## Products

### Models & Materials

- A Model: SECURASHUTTER
- B Curtain: Constructed with a two piece extruded aluminium slat forming a continuous hinge across the doorway, retained by nylon clips at either end of the slats to prevent lateral movement and providing smooth operation within the guides. Perforated slats using 4.5mm holes allowing 50% airflow are optional.
- C Roller Drum: Manufactured from spiral ducted tube and designed to give minimal deflection over the span. The tube shall revolve around the steel tubular shaft with self-lubricating drum wheels and will have helical torsion springs to counter balance the curtain weight throughout the operation.
- D Locking: A two-way mortice lock is mounted centrally within the bottom rail. Optional waist high locking is available.
- E Opening Size: Up to 4000mm high x 4000mm wide.
- F Finish: Standard finish is clear anodized. Anodizing in colours is an optional extra.
- G Operation: Manual hand operation is standard but can be fitted with a key switch operated 240v motorized unit which has a battery back-up for emergency use in case of power failure. NOTE: A 240v power point is required to be supplied and fitted by others next to each motor unit.

