



## DYNASTY 9100 SERIES (RIGHT ANGLED STACK NO FLOOR TRACK REQUIRED)



Melbourne	ph: (03) 9739 5222	fax: (03) 9739 5599
Sydney	ph: (02) 9899 2216	fax: (02) 9899 2246
Brisbane	ph: (07) 3805 8055	fax: (07) 3805 8015
Perth	ph: (08) 9343 8329	fax: (08) 9343 1725
Adelaide	ph: (08) 8326 2266	fax: (08) 8384 3570

**FREECALL 1800 651 649**

All openings for the Dynasty must be square & level & prepared to manufacturer's tolerances. Specification correct at time of printing. May alter without notice.



## DYNASTY 9100 SERIES (RIGHT ANGLED STACK NO FLOOR TRACK REQUIRED)

Dynamic's **DYNASTY® RANGE** of sliding closures are versatile and easy to operate. There are no floor tracks, removable mullions, or the need for complicated bulkheads. The **DYNASTY® RANGE** of doors give great flexibility in design and can be operated without the need for costly motorisation. Our products suit a variety of internal or external situations such as bars, receptions, gaming areas and cafés and are well suited to wide openings.

### SPECIFICATIONS

Supply and install **DYNASTY® Model 9100** by Dynamic Closures (specify).

### WORK EXCLUDED

The general contractor shall supply adequate wood or metal supports. Minimum structural capacity to support (145kg per linear metre of door).

### CONSTRUCTION

Meeting stiles shall be interlocking extruded aluminium members (32mm x 73mm). Sections shall be extruded from aluminium and constructed in accordance with details shown on shop drawings. Should fixed panels be required they shall be of matching construction. Brush weather seal at floor optional.

### PANELS

Available in the following materials:

- 6.38mm Clear Laminated Glass
- 18ga. Perforated (51%) Visibility Panels

Note: Minimum panel width 600mm. Conditions apply.

### TRACK

Track shall be heavy-duty extruded aluminium [ 38mm (h) x 36mm (w) – two tracks side by side ] and shall be surface mounted or recessed as required (specify).

### FINISH

All models are offered in our standard high quality clear anodised finish, or standard powder coat finishes.

### HARDWARE

To be Dynamic's heavy duty auto retractable cylinder locks on access panels. All other panels shall be secured with a conveniently located shootbolt system that will lock into a specially designed dust resistant floor socket.

### LAYOUT

**STACK WIDTH:** Panel size plus 70mm

**STACK DEPTH:** 70mm per panel – minimum pocket depth 300mm

Example of a 914mm Panel (Nominal Size):

PANELS	STACK WIDTH	STACK DEPTH
3	984mm	300mm min.
7	984mm	490mm
10	984mm	700mm

- > Egress available at position A only (lead panel off wall, left or right)
- > It is imperative that ceiling and floor are level.
- > Stacks left and/or right off wall.
- > Also available in bi-part stacking half left & half right.

### RIGHT ANGLE STACK (MAX HEIGHT 3600mm)

